Nova H Workstation





NOVA H desks



H 620-850



W 800

FEATURES

- Manual height adjustment according to individual needs
- Easy to assemble and disassemble "metal to metal" construction
- Just one tool for assembling (DIN911 S5)

QUALITY STANDARD

- LST EN 527-1:2011
- LST EN 527-2:2017
- LST EN 1730:2012

TECHNICAL INFORMATION

Desktop

- 25 mm MFC (melamine) with 2 mm ABS edging;
- 10 mm gap between the legs and the desktop;
- 40 mm gap between the desktops in back to back benches (depth of benches – 1440/1640).

Metal beam

- Metal tube 40x20 mm;
- With welded metal plates for leg fixing;
- Powder coated metal, colour matches the legs.

Legs

- Welded metal tube 40x40 mm;
- Powder coated metal;
- Plastic feet (without levelling);
- Manual height adjustment (fixed with bolts).

Leg type



GUARANTEE

• 5 years



Desktop type



Plain desktop



Desktops with a scallop for wire management



Desktops with a cut-out for grommet and wire management

Must be ordered

(for desktop with cut-out)



Metal grommet: 317x119 mm, H=27 mm



Optional





Cable clips



Cable ducts

Power socket blocks Cable trays

294 Kifisias Av., 15232 Chalandri - Greece - T 2106844905 - E. info@asset.gr - asset.gr