

Project Floors LVT
Vinyl Flooring

asset
space becomes place

floors@home/20

floors@home/30

floors@home/40

| Covering type according to ISO 10582 | Heterogeneous Planks / Tiles, type 1 | | |
|---|--|---------------------------|------------------------|
| Number of colours | 28 planks / 7 tiles | 77 planks / 27 tiles | 21 planks / 4 tiles |
| Packaging per box/pallet | 3.34 m ² /240.48 m ² 600x600 mm: 3.24 m ² /233,28 m ² | | |
| Performance classification EN ISO 10582 / ISO 10874 | 22 | 23, 31 | 23, 32, 41 |
| Total thickness ISO 24346 | 2.0 mm | | |
| Wearlayer thickness ISO 24340 | 0.2 mm | 0.3 mm | 0.4 mm |
| Surface treatment | yes/PU | | |
| Bevelled edges | no | yes (depending on design) | |
| Total weight ISO 23997 | 3.20 kg/m ² | 3.51 kg/m ² | 3.35 kg/m ² |
| Residual indentation ISO 24343-1 | ≤ 0.1 mm* | | |
| Dimensional stability ISO 23999 | ≤ 0.15 %* | | |
| Castor chair suitability ISO 4918 | yes – using EN 12529, type W | | |
| Underfloor heating EN 1264-2 | suitable up to 28°C | | |
| Behaviour to fire EN 13501-1 | Bfl-s1 | | |
| Resistance to thermal conductivity ISO 8302/ EN 12667 | 0.02 m ² K/W | | |
| Electrical propensity when walked upon EN 1815 | < 2 kV | | |
| Impact sound improvement ISO 10140-3 | 2 dB | | |
| Colour fastness to artificial light ISO 105-B02/02 | ≥ 7 | | |
| Electrostatic characteristics EN 1081 | > 10 ¹² | | |
| Chemical resistance ISO 26987 | conforms** | | |
| Slip resistance | R9 to R10 (depending on design resp. emboss: details available on request) | | |
| Adhesive recommendation | see installation instruction | | |
| Maintenance/Cleaning recommendation | Dr. Schutz | | |

* Averaged value

(Date: 01/01/2019)

** Vis-à-vis the short-term effects of normal, domestic agents.

Please also note the installation and cleaning and care instructions.



