

Project Floors LVT
Vinyl Flooring

asset
space becomes place

floors@work/55

floors@work/80

| Covering type according to EN ISO 10582 | Heterogeneous Planks / Tiles, type 1 | |
|---|--|------------------------|
| Number of colours | 78 planks / 31 tiles | 10 planks |
| Packaging per box/pallet | 3.34 m ² /200.40 m ² 600x600 mm: 3.24 m ² /194.40 m ² | |
| Performance classification EN ISO 10582 / ISO 10874 | 23, 33, 42 | 23, 34, 43 |
| Total thickness ISO 24346 | 2.5 mm | |
| Wearlayer thickness ISO 24340 | 0.55 mm | 0.8 mm |
| Surface treatment | yes/PU | |
| Bevelled edges | yes (depending on design) | |
| Total weight ISO 23997 | 3.81 kg/m ² | 3.72 kg/m ² |
| Residual indentation ISO 24343-1 | ≤ 0.1 mm* | |
| Dimensional stability ISO 23999 | ≤ 0.15 %* | |
| Castor chair suitability ISO 4918 | yes – using EN 12529, Typ W | |
| Underfloor heating EN 1264-2 | suitable up to 28°C | |
| Behaviour to fire EN 13501-1 | Bfl-s1 | |
| Resistance to thermal conductivity ISO 8302 / EN 12667 | 0.02 m ² K/W | |
| Electrical propensity when walked upon EN 1815 | < 2 kV | |
| Impact sound improvement ISO 10140-3 | 4 dB | |
| Colour fastness to artificial light ISO 105-B02/2 | ≥ 7 | |
| Electrostatic characteristics EN 1081 | > 10 ¹² | |
| Chemical resistance ISO 26987 | conforms** | |
| Slip resistance | R9 to R10 (depending on design resp. emboss: details available on request) | |
| Adhesive recommendation | see installation instruction | |
| Maintenance/Cleaning recommendation | Dr. Schutz | |

* Averaged value

(Date: 01/01/2019)

** Vis-à-vis the short-term effects of normal, domestic agents.

Please also note the installation and cleaning and care instructions.



